



Container Compliance Corp.

5151 Denison Avenue • Cleveland, Ohio 44102-5827

Phone: 216/961-0035 • Fax 216/961-5809

September 19, 2012

Attn: Bill Naumovski:

Please consider the following our closure notifications for 55-gallon tight head poly drums:

1. Bungs must be fitted with gaskets appropriate to the bung size and design.
2. Bungs must be placed in the appropriate openings (buttress bungs in buttress holes, fine thread bungs in fine thread holes.)
3. 2" bungs must be tightened to a torque level of 25 ft. lbs. for tamperproof bungs and 20 ft. lbs. for all other 2" bungs.

And for 55-gallon open head poly drums:

1. Bungs must be fitted with gaskets appropriate to the bung size and design.
2. Bungs must be placed in the appropriate openings (buttress bungs in buttress holes, fine thread bungs in fine thread bung holes.)
3. 2" bungs must be tightened to a torque level of 30 ft. lbs. and 3/4" bungs torqued to 9 ft. lbs.
4. Place metal ring around drum head and lip, compress lid to fit and seal.
5. Close by pressing tab downward through eye of lever lock ring.

Regards,

A handwritten signature in black ink, appearing to read 'Dan Mackall', with a long horizontal line extending to the right.

Dan Mackall